

Mechanized Irrigation

LOW PRESSURE - HIGH PERFORMANCE



AGRICULTURAL IRRIGATION | A Hunter Industries Company
Learn More. Visit senninger.com

Senninger®

Mechanized Irrigation

Senninger®

WOBBLEERS®

i-Wob2 (black)



Flow: 0.8 - 18.35 gpm (182 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Droplet size: Medium

i-Wob2 (grey)



Flow: 2.24 - 18.35 gpm (509 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Droplet Size: Small

i-Wob2 (blue)



Flow: 0.8 - 18.35 gpm (182 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Droplet Size: Medium

i-Wob2 (white)



Flow: 2.51 - 18.35 gpm (570 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Droplet Size: Large

Xi-Wob (blue)



Flow: 1.09 - 15.78 gpm (248 - 3584 L/hr)
Pressure: 10 - 15 psi (0.69 - 1.03 bar)
Droplet Size: Medium

Xi-Wob (black)



Flow: 2.24 - 15.78 gpm (509 - 3584 L/hr)
Pressure: 10 - 15 psi (0.69 - 1.03 bar)
Droplet Size: Large

Xi-Wob (grey)



Flow: 2.24 - 15.78 gpm (509 - 3584 L/hr)
Pressure: 10 - 15 psi (0.69 - 1.03 bar)
Droplet Size: Small

Xcel-Wobbler TOP



Flow: 0.80 - 14.98 gpm (182 - 3402 L/hr)
Pressure: 10 psi (0.69 bar)
Droplet Size: Large

LDN®

LDN - Spray



Flow: 0.27 - 21.2 gpm (61 - 4815 L/hr)
Pressure: 6 - 20 psi (0.41 - 1.38 bar)
Several deflector pad options

LDN - LEPA Bubbler



Flow: 0.27 - 18.35 gpm (61 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Several deflector pad options

LDN - LDN Shroud



Flow: 0.27 - 18.35 gpm (61 - 4168 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)
Several deflector pad and insert options

LDN - Part Circle



Flow: 0.62 - 10.35 gpm (141 - 2351 L/hr)
Pressure: 6 - 15 psi (0.41 - 1.03 bar)

SPRAYS

Super Spray®



Flow: 0.27 - 29.96 gpm (61 - 6805 L/hr)
Pressure: 6 - 40 psi (0.41 - 2.76 bar)
Several deflector pad options

End Spray



Flow: 8.1 - 48.9 gpm (1840 - 11106 L/hr)
Pressure: 10 - 25 psi (0.69 - 1.72 bar)

Impact Sprinkler



Flow: 1.87 - 36.0 gpm (425 - 8177 L/hr)
Pressure: 30 - 60 psi (2.07 - 4.14 bar)

Goosenecks



Single max flow: 20 gpm (4543 L/hr)
Double max flow: 15 gpm (3406 L/hr) per side

REGULATORS AND ACCESSORIES

PRL



Flow: 0.5 - 8 gpm (114 - 1817 L/hr)
Pressure: 6 - 40 psi (0.41 - 2.76 bar)

PSR-2




0.5 - 15 gpm (114 - 3407 L/hr)
Pressure: 6 - 50 psi (0.41 - 3.45 bar)

PMR-MF



Flow: 2 - 20 gpm (454 - 4542 L/hr)
Pressure: 6 - 60 psi (0.41 - 4.14 bar)

Truss Rod Hose Slings



Five color-coded truss rod sizes.
For use with 125-degree goosenecks.

Boom System



For pivot towers and overhangs

Ball Valve and Fittings



Several Models Available

Magnum Weight & One Weight



Fits Senninger's and other Manufacturers' Applicators

Pressure Drop



Provides a quick and easy check of end-of-system pressure.
Freeze-Proof design.